

SD3092

13W Adjustable Surface Spot

Description

Spot Light for indoor use;
Adjustable head;
Baffle available in finishing: Matt Black/Matt White;

Finish
Black/White

Material
Aluminium



18D

28D

39D

TECHNICAL CHARACTERISTICS

Light source

Light source: Citizen COB
Output (W): 350mA 31V 10.85W
Total power consumption (W): 12.76W
Color temperature: 2700K/3000K/4000K
CRI: 90
Photobiological risk: RG1
Real Lumen: 780
Qty Leds: 1
Lm/Real W: 61
Life Time: 50.000h L90B20
MacAdam steps: 3
UGR: <11


GEAR

This product incl
HEP G5R15W350LRP power
supply(on/off).

Phase cut/DALI/0-10V drivers are
available upon request.

Luminaire

IP54 for indoor using
crossing: No
Warranty: 5 Years



LIGHT DISTRIBUTION for 3000K spot 18°

h(m)	E(lx)	Ø(m)
1	4400	Ø0.32
2	1100	Ø0.64
3	488.9	Ø0.96
4	275.0	Ø1.29
5	176.0	Ø1.61

LIGHT DISTRIBUTION for 3000K medium 28°

h(m)	E(lx)	Ø(m)
1	2761	Ø0.52
2	690.2	Ø1.03
3	306.8	Ø1.55
4	172.6	Ø2.07
5	110.4	Ø2.58

LIGHT DISTRIBUTION for 3000K wide 39°

h(m)	E(lx)	Ø(m)
1	1797	Ø0.71
2	449.2	Ø1.42
3	199.7	Ø2.12
4	112.3	Ø2.84
5	71.88	Ø3.55



The photograph may not match the reference exactly. Please read the product description to identify the finish.